





# **ENVIRONMENTAL PRODUCT DECLARATION**

# IN ACCORDANCE WITH EN 15804+A2 & ISO 14025

# EPD HUB, HUB-1730

Published on 26 July 2024, last updated on 26 July 2024, valid until 26 July 2029.

14 MPa (Type I+35% NP)-DSP. Saudi Readymix Concrete Co, Joint Stock Company Unlisted



## **MANUFACTURER AND SITE**

MANOTACTORES	TAITE SITE
Manufacturer	Saudi Readymix Concrete Co, Joint Stock Company Unlisted
Address	2nd Industrial City, Dammam, Kingdom of Saudi Arabia, P.O Box 8635, 34333, , , Dammam, , SA
Contact details	info@saudireadymix.com.sa
Website	www.saudireadymix.com.sa
Place of production	Saudi Arabia
Period for data	1.1.2023 - 31.12.2023

## **EPD STANDARDS, SCOPE AND VERIFICATION**

Program operator EPD Hub, hub@epdhub.com  Reference standard EN 15804+A2 and ISO 14025
Poforonco standard EN 15904±A2 and ISO 14025
NEICICINE Standard LIV 13004TAZ dilu i30 14023
PCR EPD Hub Core PCR version 1.1, 5 Dec 2023
cPCR EN 16757 Product Category Rules for concrete and concrete elements
Sector Construction product
Category of EPD Third party verified EPD
Scope of the EPD Cradle to gate with options, A4-A5, and modules C1-C4, D
EPD author Khaldoon Slaiai - Saudi Readymix
EPD verification Independent verification of this EPD and data, according to ISO 14025:  ☐ Internal verification ☑ External verification
EDD verifier Vinus 7hong of an authorized verifier acting
EPD verifier Xinyuan Zhang, as an authorized verifier acting for EPD Hub Limited

## **PRODUCT SPECIFICATION**

Product name	14 MPa (Type I+35% NP)-DSP.
Concrete type	Ready-mix concrete
Product standards	EN 206-1
Compressive strength class	C16/20
Strength evaluation days	28 days
Exposure class	XD3 -
Product description	(0103-APPZ9FAA001) - (SRM- 1)14MPA+35%NP@56Days-190±30mm Slump-20mm Agg-CY Dammam Stadium Project. Supplementary Cementitious Materials: 35% Saudi Natural Pozzolans

## **ENVIRONMENTAL DATA SUMMARY**

Declared unit	1 cubic meter	
Declared unit mass, kg	2337	
Global Warming Potential A1-A	13	
GWP-total (kg CO₂e)	2,21E+02	
GWP-fossil (kg CO₂e)	2,20E+02	
GWP-biogenic (kg CO₂e)	1,57E-01	
GWP-luluc	8,24E-02	

The manufacturer has the sole ownership, liability, and responsibility for the EPD. EPDs within the same product category but from different programs may not be comparable. EPDs of construction products may not be comparable if they do not comply with EN 15804 and if they are not compared in a building context





#### **SYSTEM BOUNDARY**

This EPD covers the life-cycle modules listed in the following table.

	Product stage		Coocingly ambe	Assembly stage					ć	End of life stage		Beyond the system boundaries				
A1	A2	А3	A4	A5	B1	B2	В3	B4	B5	В6	В7	C1	C2	C3	C4	D
x	x	x	x	x	M N D	M N D	M N D	M N D	M N D	M N D	M N D	x	x	x	x	x
Raw materials	Transport	Manufacturing	Transport	Assembly	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	Deconstr./demol.	Transport	Waste processing	Disposal	Reuse, Recovery, Recycling

Modules not declared = MND. Modules not relevant = MNR.

#### **CUT-OFF CRITERIA**

The study does not exclude any modules or processes which are stated mandatory in the reference standard and the applied PCR. The study does not exclude any hazardous materials or substances. There is no neglected unit process more than 1% of total mass or energy flows. The module specific total neglected input and output flows also do not exceed 5% of energy usage or mass.

## **ALLOCATION, ESTIMATES AND ASSUMPTIONS**

All allocations are done as per the reference standards and the applied PCR. In this study, allocation has been done in the following ways:

Data type	Allocation
Raw materials	No allocation
Packaging materials	Not applicable
Ancillary materials	Allocated by mass
Manufacturing energy and waste	Allocated by mass

#### **AVERAGES AND VARIABILITY**

This EPD is product and factory specific and does not contain average calculations.



#### PRODUCT RAW MATERIAL MAIN COMPOSITION

The product is a ready-mix concrete consisting of aggregates, cement, filler, admixtures, and water. Main material categories as per EPD Hub GPI shown below:

Raw material category	Amount, mass- %	Material origin
Metals	0	NA
Minerals	93.4	Various
Fossil materials	0.25	Various
Bio-based materials	0	NA

#### **SUBSTANCES, REACH - VERY HIGH CONCERN**


The product does not contain any REACH SVHC substances in amounts greater than 0.1% (1000 ppm).

Substances of very high concern	EC	CAS
NA	NA	NA

#### **BIOGENIC CARBON CONTENT**

Product's biogenic carbon content at the factory gate

Biogenic carbon content in product, kg C
--







# PRODUCT LIFE CYCLE

## **MANUFACTURING (A1-A3)**

The environmental impacts considered for the product stage cover the manufacturing of raw materials used in the production. Also, fuels used by machines, and handling of waste formed in the production processes at the manufacturing facilities are included in this stage. The study also considers the material losses occurring during the manufacturing processes as well as losses during electricity transmission.

Ready-mix concrete production starts by transporting the binders, aggregates, and additives to the manufacturing site and storing them into closed silos and containers. The aggregates are then dosed onto a scale and transferred to a concrete mixer. In the mixer, cement is added to the aggregates, after which the material is mixed dry. Water and additives are then added to the mixture, followed by wet mixing. After mixing, the concrete mass is unloaded from the mixer into the tank of the concrete mixer truck, which is transported to the construction site.

No packaging is included as the product is transported with mixer trucks.

#### **TRANSPORT AND INSTALLATION (A4-A5)**

The concrete is transported to the building site using an average lorry. Transportation impacts occurred from final products delivery to construction site cover fuel direct exhaust emissions, environmental impacts of fuel production, as well as related infrastructure emissions (A4).

Installation includes the energy used for concrete application. This consists of the energy spent by a concrete mixer truck and a concrete pump. A production loss of 3% at installation is assumed (A5).

#### PRODUCT USE AND MAINTENANCE (B1-B7)

This EPD does not cover the use phase. Air, soil, and water impacts during the use phase have not been studied.

### PRODUCT END OF LIFE (C1-C4, D)


At the end-of-life, the concrete is assumed to be a part of a concrete building which demolished with machinery that consumes energy in the form of diesel (C1).

The concrete blocks gotten after the demolition are delivered 50 km by a lorry to the nearest construction waste treatment (C2). It is assumed that 100% of the demolished concrete is transported to a site where this waste is processed by, crushing the blocks to gravel. About 70% of the concrete can be recycled this way (C3). The remaining 30% of concrete is assumed to be sent to the landfill for disposal (C4). The crushed concrete received from waste treatment can be used as a replacement for virgin gravel or for raw materials in road construction (D). The process losses of the waste treatment plant are assumed to be negligible.

#### LCA SOFTWARE AND BIBLIOGRAPHY

The LCA and EPD have been prepared according to the reference standards and ISO 14040/14044. Ecoinvent v3.8 and One Click LCA databases were used as sources of environmental data

#### **MANUFACTURING PROCESS DIAGRAM (A1-A3)**







# **ENVIRONMENTAL IMPACT DATA**

## CORE ENVIRONMENTAL IMPACT INDICATORS - EN 15804+A2, PEF

Impact category	Unit	A1	A2	А3	A1-A3	A4	A5	B1	B2	В3	B4	B5	В6	В7	C1	C2	С3	C4	D
GWP – total <sup>1)</sup>	kg CO₂e	1,89E+02	2,43E+01	7,12E+00	2,21E+02	8,70E+00	1,43E+01	MND	4,08E+00	1,06E+01	6,46E+00	3,65E+00	-1,30E+01						
GWP – fossil	kg CO₂e	1,89E+02	2,43E+01	7,12E+00	2,20E+02	8,70E+00	1,43E+01	MND	4,08E+00	1,06E+01	6,57E+00	3,69E+00	-1,31E+01						
GWP – biogenic	kg CO₂e	1,57E-01	0,00E+00	-3,13E-04	1,57E-01	0,00E+00	0,00E+00	MND	0,00E+00	0,00E+00	-1,10E-01	-4,69E-02	1,10E-01						
GWP – LULUC	kg CO₂e	7,32E-02	8,96E-03	3,08E-04	8,24E-02	3,13E-03	3,48E-03	MND	4,06E-04	3,81E-03	6,54E-04	3,49E-03	-1,81E-02						
Ozone depletion pot.	kg CFC-11e	7,79E-06	5,59E-06	1,29E-06	1,47E-05	2,08E-06	2,11E-06	MND	8,73E-07	2,53E-06	1,40E-06	1,49E-06	-1,10E-06						
Acidification potential	mol H⁺e	6,15E-01	1,03E-01	6,59E-02	7,84E-01	3,63E-02	9,93E-02	MND	4,24E-02	4,43E-02	6,83E-02	3,47E-02	-8,57E-02						
EP-freshwater <sup>2)</sup>	kg Pe	2,16E-03	1,99E-04	4,16E-06	2,36E-03	5,95E-05	9,90E-05	MND	1,35E-05	7,26E-05	2,18E-05	3,87E-05	-7,76E-04						
EP-marine	kg Ne	1,86E-01	3,06E-02	2,32E-02	2,40E-01	1,10E-02	4,03E-02	MND	1,88E-02	1,34E-02	3,02E-02	1,20E-02	-1,85E-02						
EP-terrestrial	mol Ne	2,13E+00	3,37E-01	2,52E-01	2,72E+00	1,21E-01	4,45E-01	MND	2,06E-01	1,48E-01	3,31E-01	1,32E-01	-2,42E-01						
POCP ("smog") <sup>3)</sup>	kg NMVOCe	5,33E-01	1,08E-01	6,71E-02	7,08E-01	3,90E-02	1,22E-01	MND	5,66E-02	4,75E-02	9,11E-02	3,84E-02	-6,22E-02						
ADP-minerals & metals <sup>4)</sup>	kg Sbe	9,84E-04	5,69E-05	2,13E-06	1,04E-03	2,04E-05	3,64E-05	MND	2,07E-06	2,49E-05	3,34E-06	8,48E-06	-1,32E-04						
ADP-fossil resources	MJ	1,18E+03	3,65E+02	3,90E+01	1,59E+03	1,33E+02	1,53E+02	MND	5,49E+01	1,62E+02	8,84E+01	1,01E+02	-1,95E+02						
Water use <sup>5)</sup>	m³e depr.	2,04E+01	1,63E+00	2,77E-01	2,23E+01	6,14E-01	9,72E-01	MND	1,48E-01	7,49E-01	2,38E-01	3,21E-01	-2,59E+01						

<sup>1)</sup> GWP = Global Warming Potential. 2) EP = Eutrophication potential. Required characterisation method and data are in kg P-eq. Multiply by 3,07 to get PO4e. 3) POCP = Photochemical ozone formation. 4) ADP = Abiotic depletion potential. 5) EN 15804+A2 disclaimer for Abiotic depletion and Water use and optional indicators except Particulate matter and Ionizing radiation, human health. The results of these environmental impact indicators shall be used with care as the uncertainties on these results are high or as there is limited experience with the indicator.

## ADDITIONAL (OPTIONAL) ENVIRONMENTAL IMPACT INDICATORS - EN 15804+A2, PEF

Impact category	Unit	A1	A2	А3	A1-A3	A4	A5	B1	B2	В3	B4	B5	В6	В7	C1	C2	С3	C4	D
Particulate matter	Incidence	5,84E-06	2,80E-06	2,43E-07	8,89E-06	1,02E-06	2,66E-06	MND	1,14E-06	1,25E-06	1,40E-05	6,99E-07	-1,10E-06						
Ionizing radiation <sup>6)</sup>	kBq U235e	4,01E+00	1,74E+00	2,91E-01	6,04E+00	6,86E-01	6,71E-01	MND	2,52E-01	8,36E-01	4,06E-01	4,58E-01	-3,10E+00						
Ecotoxicity (freshwater)	CTUe	4,69E+03	3,28E+02	4,62E+01	5,06E+03	1,11E+02	2,18E+02	MND	3,30E+01	1,35E+02	5,32E+01	6,61E+01	-2,34E+02						
Human toxicity, cancer	CTUh	4,20E-08	8,06E-09	1,12E-09	5,12E-08	2,92E-09	3,94E-09	MND	1,27E-09	3,56E-09	2,04E-09	1,65E-09	-1,36E-08						
Human tox. non-cancer	CTUh	1,42E-06	3,25E-07	4,40E-08	1,79E-06	1,17E-07	1,03E-07	MND	2,39E-08	1,43E-07	3,84E-08	4,32E-08	-2,49E-07						
SQP <sup>7)</sup>	-	1,15E+03	4,20E+02	6,23E+00	1,57E+03	1,55E+02	7,62E+01	MND	7,14E+00	1,89E+02	1,15E+01	2,16E+02	-1,88E+02						

<sup>6)</sup> EN 15804+A2 disclaimer for Ionizing radiation, human health. This impact category deals mainly with the eventual impact of low dose ionizing radiation on human health of the nuclear fuel cycle. It does not consider effects due to possible nuclear accidents, occupational exposure nor due to radioactive waste disposal in underground facilities. Potential ionizing radiation from the soil, from radon and from some construction materials is also not measured by this indicator. 7) SQP = Land use related impacts/soil quality.







## **USE OF NATURAL RESOURCES**

Impact category	Unit	A1	A2	А3	A1-A3	A4	A5	B1	B2	В3	B4	B5	В6	В7	C1	C2	С3	C4	D
Renew. PER as energy <sup>8)</sup>	MJ	6,57E+01	4,11E+00	2,91E-01	7,01E+01	1,72E+00	2,78E+00	MND	3,14E-01	2,10E+00	5,05E-01	8,79E-01	-1,82E+01						
Renew. PER as material	MJ	8,02E-01	0,00E+00	-1,60E-03	8,00E-01	0,00E+00	0,00E+00	MND	0,00E+00	0,00E+00	-5,60E-01	-2,40E-01	5,60E-01						
Total use of renew. PER	MJ	6,65E+01	4,11E+00	2,89E-01	7,09E+01	1,72E+00	2,78E+00	MND	3,14E-01	2,10E+00	-5,46E-02	6,39E-01	-1,76E+01						
Non-re. PER as energy	MJ	1,15E+03	3,65E+02	9,94E+01	1,62E+03	1,33E+02	1,54E+02	MND	5,49E+01	1,62E+02	8,84E+01	1,01E+02	-1,95E+02						
Non-re. PER as material	MJ	2,82E+01	0,00E+00	-5,62E-02	2,81E+01	0,00E+00	0,00E+00	MND	0,00E+00	0,00E+00	- 1 07F±01	6 \3E±UU -	1,97E+01						
Total use of non-re. PER	MJ	1,18E+03	3,65E+02	9,93E+01	1,65E+03	1,33E+02	1,54E+02	MND	5,49E+01	1,62E+02	6,88E+01	9,28E+01	-1,75E+02						
Secondary materials	kg	2,43E-01	1,01E-01	2,41E-03	3,47E-01	3,75E-02	5,02E-02	MND	2,15E-02	4,57E-02	3,46E-02	2,13E-02	-2,15E-01						
Renew. secondary fuels	MJ	4,90E-03	1,02E-03	3,47E-05	5,96E-03	3,31E-04	3,37E-04	MND	7,02E-05	4,03E-04	1,13E-04	5,56E-04	-1,54E-03						
Non-ren. secondary fuels	MJ	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	MND	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00						
Use of net fresh water	m³	1,40E+00	4,72E-02	5,23E-03	1,45E+00	1,77E-02	5,36E-02	MND	3,34E-03	2,15E-02	5,37E-03	1,11E-01	-6,26E-01						

<sup>8)</sup> PER = Primary energy resources.

## **END OF LIFE – WASTE**

Impact category	Unit	A1	A2	А3	A1-A3	A4	A5	B1	B2	В3	B4	B5	В6	В7	C1	C2	С3	C4	D
Hazardous waste	kg	5,71E+00	4,84E-01	2,63E-02	6,22E+00	1,43E-01	3,21E-01	MND	7,35E-02	1,74E-01	1,18E-01	0,00E+00	-1,10E+00						
Non-hazardous waste	kg	1,31E+02	7,94E+00	1,76E+00	1,40E+02	2,48E+00	2,63E+01	MND	5,17E-01	3,03E+00	8,32E-01	7,01E+02	-3,42E+01						
Radioactive waste	kg	7,27E-03	2,44E-03	4,68E-04	1,02E-02	9,18E-04	1,03E-03	MND	3,87E-04	1,12E-03	6,22E-04	0,00E+00	-1,02E-03						

## **END OF LIFE – OUTPUT FLOWS**

Impact category	Unit	A1	A2	А3	A1-A3	A4	A5	B1	B2	В3	B4	B5	В6	B7	C1	C2	C3	C4	D
Components for re-use	kg	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	MND	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00						
Materials for recycling	kg	1,20E-04	0,00E+00	3,27E+00	3,27E+00	0,00E+00	4,92E+01	MND	0,00E+00	0,00E+00	1,64E+03	0,00E+00	0,00E+00						
Materials for energy rec	kg	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	MND	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00						
Exported energy	MJ	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	MND	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00						







# ENVIRONMENTAL IMPACTS – EN 15804+A1, CML / ISO 21930

Impact category	Unit	A1	A2	А3	A1-A3	A4	A5	B1	B2	В3	B4	B5	В6	В7	C1	C2	C3	C4	D
Global Warming Pot.	kg CO₂e	1,89E+02	2,40E+01	7,06E+00	2,20E+02	8,61E+00	1,42E+01	MND	4,04E+00	1,05E+01	6,50E+00	3,62E+00	-1,28E+01						
Ozone depletion Pot.	kg CFC-11e	6,24E-06	4,42E-06	1,01E-06	1,17E-05	1,64E-06	1,67E-06	MND	6,91E-07	2,01E-06	1,11E-06	1,18E-06	-9,13E-07						
Acidification	kg SO₂e	4,52E-01	7,99E-02	4,95E-02	5,82E-01	2,81E-02	7,17E-02	MND	3,02E-02	3,43E-02	4,87E-02	2,62E-02	-6,63E-02						
Eutrophication	kg PO <sub>4</sub> ³e	1,61E-01	1,82E-02	8,40E-03	1,87E-01	6,29E-03	1,82E-02	MND	7,01E-03	7,67E-03	1,13E-02	5,66E-03	-3,21E-02						
POCP ("smog")	kg C₂H₄e	1,81E-02	3,12E-03	1,68E-03	2,29E-02	1,11E-03	1,92E-03	MND	6,62E-04	1,35E-03	1,07E-03	1,10E-03	-4,56E-03						
ADP-elements	kg Sbe	6,51E-04	5,51E-05	3,82E-06	7,10E-04	1,98E-05	2,64E-05	MND	2,04E-06	2,42E-05	3,28E-06	8,36E-06	-1,30E-04						
ADP-fossil	MJ	1,18E+03	3,65E+02	9,94E+01	1,65E+03	1,33E+02	1,55E+02	MND	5,49E+01	1,62E+02	8,84E+01	1,01E+02	-1,95E+02						







# VERIFICATION STATEMENT

### **VERIFICATION PROCESS FOR THIS EPD**

This EPD has been verified in accordance with ISO 14025 by an independent, third-party verifier by reviewing results, documents and compliancy with reference standard, ISO 14025 and ISO 14040/14044, following the process and checklists of the program operator for:

- This Environmental Product Declaration
- The Life-Cycle Assessment used in this EPD
- · The digital background data for this EPD

Why does verification transparency matter? Read more online

This EPD has been generated by One Click concrete LCA EPD generator, which has been verified and approved by the EPD Hub.

#### THIRD-PARTY VERIFICATION STATEMENT

I hereby confirm that, following detailed examination, I have not established any relevant deviations by the studied Environmental Product Declaration (EPD), its LCA and project report, in terms of the data collected and used in the LCA calculations, the way the LCA-based calculations have been carried out, the presentation of environmental data in the EPD, and other additional environmental information, as present with respect to the procedural and methodological requirements in ISO 14025:2010 and reference standard.

I confirm that the company-specific data has been examined as regards plausibility and consistency; the declaration owner is responsible for its factual integrity and legal compliance.

I confirm that I have sufficient knowledge and experience of construction products, this specific product category, the construction industry, relevant standards, and the geographical area of the EPD to carry out this verification.

I confirm my independence in my role as verifier; I have not been involved in the execution of the LCA or in the development of the declaration and have no conflicts of interest regarding this verification.

Xinyuan Zhang, as an authorized verifier acting for EPD Hub Limited 26.07.2024





